

Chicago Pneumatic CP0611P RLS Impact Wrenches - #5 Spline 1220-2440NM

The Best Super Industrial with Spline #5. Best impact to target big bolts on very demanding industries thanks to Spline #5. Spline #5: avoid loss of torque, reduce vibrations, increase durability of anvil. Operator comfort and control thanks to perfect ergonomic design even at VERY high torque. Constant & progressive Torque due to the 2-Jaw clutch. Unmatched durability with reliable mechanism & durable housing. Excellent for Heavy Industrial Maintenance Production applications. Range: 1220 - 2440 Nm 900 - 1800 ft.lbs



Specifications	Details
Power/weight ratio	Metric: 361 Nm/kg Imperial: 121.2 ft.lb/lb
Side to center	Metric: 46 mm Imperial: 1.81"
Sound pressure	102 db(A)
Sound Power	113 db(A)
Air inlet thread size	1/2"
Range Metric	900 - 1800 ft.lbs
Net weight	Metric: 10.5 kg Imperial: 23.1 lb
Product Number	6151590060
Brand	Chicago Pneumatic
Length	Metric: 272 mm Imperial : 10.7"
Square Drive	#5 spline
Model Number	CP0611P RLS
Maximum Torque (reverse)	Metric: 3790 Nm Imperial: 2800 ft.lbs
Vibration uncertainty (K)	4.7 m/s ²
Vibration	16.8 m/s ²
Free Speed	3500 rpm