

Chicago Pneumatic CP797SP6 Impact Wrenches - #5 Spline 200-1225NM

The truck tire Reference. The undisputed market leader. Long known as the workhorse of the truck tire industry. Clutch delivers smooth operation and extreme durability. Ideal for high volume work on trucks, buses, and heavy equipment. Range: 200 - 1225 Nm 150 - 900 ft.lbs



Specifications	Details
Square Drive	#5 spline
Average air consumption	Metric: 4.7 l/s Imperial: 10 cfm
Model Number	CP797SP6
Range Imperial	150 - 900 ft.lbs
Net weight	Metric: 13.49 kg Imperial: 29.75 lb
Air inlet thread size	1/2"
Power/weight ratio	Metric: 140.7 Nm/kg Imperial: 47.1 ft.lb/lb
Sound Power	121 db(A)
Vibration	12.8 m/sÂ²
Sound pressure	110 db(A)
Actual air consumption	Metric: 18.9 l/s Imperial: 40 cfm
Min. Hose Size	Metric: 13 mm Imperial: 1/2"
Product Number	T018653
Brand	Chicago Pneumatic
Maximum Torque (reverse)	Metric: 1898 Nm Imperial: 1400 ft.lbs
Range Metric	200 - 1225 Nm
Free Speed	4200 rpm
Vibration uncertainty (K)	4.3 m/sÂ²