

Chicago Pneumatic CP6300 RSR 3/8 Impact Wrenches 54-203NM

Powerful, lightweight and durable 3/8 for industrial applications. Industrial Maintenance and Production. Durable housing for versatile applications. Powerful torque delivery. Compact and lightweight for operator comfort. Easy to service. Range: 54 - 203 Nm 40 - 150 ft.lbs



Specifications	Details
Brand	Chicago Pneumatic
Length	Metric: 152 mm Imperial : 5.98"
Square Drive	3/8"
Product Number	T025285
Free Speed	6800 rpm
Sound pressure	90 db(A)
Actual air consumption	Metric: 6.6 l/s Imperial: 14 cfm
Sound Power	101 db(A)
Power/weight ratio	Metric: 151.9 Nm/kg Imperial: 51.4 ft.lb/lb
Net weight	Metric: 1.6 kg Imperial: 3.5 lb
Air inlet thread size	1/4"
Model Number	CP6300 RSR
Side to center	Metric: 32 mm Imperial : 1.26"
Vibration	5 m/s ²

Specifications	Details
Range Imperial	54 - 203 Nm
Vibration uncertainty (K)	1.6 m/s
Maximum Torque (reverse)	Metric: 243 Nm Imperial: 180 ft.lbs

