

Chicago Pneumatic CP6500-RSR 1/2 Impact Wrenches 170-680NM

The best heavy-duty 1/2 for the toughest jobs !. Best performer for Industrial Maintenance and Production applications. Operator comfort and control even on high torque. Extremely robust for tough environments. Compact 3-part construction for easy maintenance. Range: 170 - 680 Nm 125 - 502 ft.lbs



Specifications	Details
Power/weight ratio	Metric: 320.8 Nm/kg Imperial: 107.8 ft.lb/lb
Range Metric	170 - 680 Nm
Range Imperial	125 - 502 ft.lbs
Net weight	Metric: 2.65 kg Imperial: 5.8 lb
Vibration uncertainty (K)	2 1/2 m/s ²
Working Torque Range (fwd)	Metric: 170 - 680 Nm Imperial: 125 - 502 ft.lbs
Free Speed	6400 rpm
Air inlet thread size	1/4"
Sound Power	107 db(A)
Sound pressure	96 db(A)
Actual air consumption	Metric: 11.8 l/s Imperial: 25 cfm
Product Number	T025216
Brand	Chicago Pneumatic
Maximum Torque (reverse)	Metric: 850 Nm Imperial: 625 ft.lbs

Specifications	Details
Length	Metric: 178 mm Imperial: 7"
Square Drive	1/2"
Model Number	CP6500-RSR
Side to center	Metric: 32 mm Imperial: 1.26"
Vibration	8 m/s ²

