

Chicago Pneumatic CP7748TL 1/2 Impact Wrenches 90-96NM

Torque Limited in forward and Extreme Torque in reverse. Torque limited in forward: 60/70 ft. Lbs. - 90/100 Nm. Full power in reverse. One Hand Operation: 2 power setting positions. Insulation & Comfort: Contoured comfort grip handle instead of TPR injected in handle. Low sound level. Suited for all light vehicle tire changing applications. Range: 90 - 96 Nm 66 - 70 ft.lbs



Specifications	Details
Vibration	4.8 m/s ²
Maximum Torque (reverse)	Metric: 1250 Nm Imperial: 920 ft.lbs
Range Metric	90 - 96 Nm
Range Imperial	66 - 70 ft.lbs
Net weight	Metric: 2.2 kg Imperial: 4.8 lb
Vibration uncertainty (K)	1 1/2 m/s ²
Length	Metric: 200 mm Imperial: 7.8"
Min. Hose Size	Metric: 10 mm Imperial: 3/8"
Air inlet thread size	1/4"
Power/weight ratio	Metric: 568.2 Nm/kg Imperial: 192.1 ft.lb/lb
Sound Power	97 db(A)
Actual air consumption	Metric: 10 l/s Imperial: 5 1/2 cfm
Average air consumption	Metric: 2 1/2 l/s Imperial: 5 1/2 cfm
Side to center	Metric: 38 mm Imperial: 1 1/2"

Specifications	Details
Model Number	CP7748TL
Square Drive	1/2"
Free Speed	8200 rpm
Product Number	8941077484
Brand	Chicago Pneumatic
Sound pressure	86 db(A)

