

Chicago Pneumatic CP3512 5 Orbital sanders

Ergonomic & powerful. Operator comfort with ergonomic palm shape. Productivity increased with low vibration level. Powerful and ergonomic palm shape for vertical and horizontal applications. 3/16 (5 mm): great for surface preparation from body filler to paint primer



Specifications	Details
Actual air consumption	Metric: 7.6 l/s 453 l/mn Imperial: 16 cfm
Power	Metric: 210 W Imperial: 0.3 hp
Brand	Chicago Pneumatic
Height over spindle	Metric: 105 mm Imperial: 4.1"
Orbit diameter	Metric: 5 mm Imperial: 3/16"
Free speed air consumption	Metric: 9.2 l/s Imperial: 19.5 cfm
Net weight	Metric: 0.78 kg Imperial: 1.38 lb
Paper size	Metric: 125 mm Imperial: 5"
Product Number	6151933512
Free Speed	12000 rpm
Min. Hose Size	Metric: 10 mm Imperial: 3/8"
Air inlet thread size	1/4"
Sound Power	90.8 db(A)
Sound pressure	81 db(A)

Specifications	Details
Average air consumption	Metric: 3.8 l/s 227 l/mn Imperial: 8 cfm
Model Number	CP3512
Vibration uncertainty (K)	1.3 m/s ²
Vibration	3 m/s ²
Pad diameter	Metric: 125 mm Imperial: 1.38 lb
Vibration ISO	ISO-28927-3
Pad type Hook & Loop	yes
Pad type PSA	no
Self vacuum	x
Vacuum	Self vacuum
Pad holes number	6
Spindle thread	5/16-24

