

UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com Tel: +966 (0) 3 834 4264

Fax: +966 3 834 4538

Kern FKT 1L 60kg Bench scale

80 memories for each operation mode, e.g., for checkweighing, PRE-TARE, reference weight, target weight when dispensing etc. Convenient recipe weighing: 99 recipes each with 10 components each can be stored in plain text. If one recipe ingredient is overweight, then the practical recipe adjustment function for when dosages are exceeded automatically calculates the new target weights of the other ingredients. The actual and target values and the proportionate percentage can then be printed. The recipes can be generated easily in an Excel list at the PC and transferred to the balance using the RS-232 interface. Alternatively, the recipes can also be entered directly using the keypadMultiplier function: recipes where the ingredients have been recorded as percentages can easily be multiplied when entering the new target weight is entered, target weight, which is ideal for the production of larger containers, bulk packs etc. Rapid function for shortened stabilisation time with reduced readout16 print forms which can store up to 20 different information, such as, e.g., date, time, operator, item, net, tare, gross, PCS, target weight, PRE-TARE etc. The print forms can be generated easily in an Excel list in the PC and transferred to the balance using the RS-232 interfaceControl outputs (optocoupler, digital I/O) to connect relays, signal lamps, valves etc. (35 V / 80 mA)Hook for underfloor weighing of hanging loads standard for models with weighing plate size For particularly high counting accuracy, there is an option of combining the KERN FKT range with a high-precision reference balance to make a counting system, please enquireModes Weighing Counting Dispensing Recipe weighing Checkweighing Totalising with daily total Percentage determination Animal weighing Surface weight Density determination, only with, not for Rapid function, not for



Specifications	Details
Weighing range [Max]	$60~\mathrm{kg}$
Weighing system	Strain gauge
Weighing units	ct dwt g kg lb mo oz ozt t tl (HK) tl (Singap. Malays) tl (Tw)
Maximum humidity	80 %
Maximum operating temperature	40 °C

E-Mail : gentech@eim.ae Website : www.generaltech.ae



UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706

SAUDI

Mathews@generaltechsaudi.com Tel: +966 (0) 3 834 4264

Fax: +966 3 834 4538

weight 7 ndicator: ye ing screw feet: ye adapter/adapter included: C ting time (Backlight on): 1 rgeable battery: R	10 °C 7.6 kgs 7es 7EB EURO
ndicator: ing screw feet: adapter/adapter included: Cing time (Backlight on): rgeable battery: R	ves Ves CH EURO
ing screw feet: adapter/adapter included: cing time (Backlight on): rgeable battery: R	ves CH EURO
adapter/adapter included: Cing time (Backlight on): 10 11 12 13 14 15 16 16 17 17 17 18 18 18 18 18 18 18	CH EURO
rgeable battery: R	
rgeable battery:	10 h
ing with tolerance range:	Rchrg. battery optional - intern
	res
ange: 6	60 kg
ng function:	ves .
tage determination ye	ves .
ng resolution 6	50000
m piece weight at piece counting (Laboratory 1	l g
nm piece weight at piece counting (Normal)	10 g
on to save totals:	ves .
ARE function:	ves .
by function:	ves .
up time 2	2 h
sation time 3	3 s
tion 6	50000
ducibility 1	l g
mended adjusting weight 5	50 kg (E2); 10 kg (E2)
ut [d] 1	l g
ity 2	2 g
ring time (Backlight off)	20 h
ment options E	External calibration
isplay: ye	700

P.O Box 25898 Sharjah United Arab Emirates

Phone : 06-5436933/06-5436733

Fax : 06-5437077

E-Mail:gentech@eim.ae Website: www.generaltech.ae



UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com Tel: +966 (0) 3 834 4264

Fax: +966 3 834 4538

Specifications	Details
Suspended weighing	Hook
Operating time	20 h
Input voltage	100 V - 240 V
Charging time	10 h
Display digit height:	4 mm
Weighing surface (WxD):	340 mm x 240 mm
Material weighing plate:	stainless steel
Dimensions housing (WxDxH):	350 mm x 390 mm x 120 mm
Net weight	6.5 kgs
Model Number	FKT 1L
Brand	Kern
Product Number	FKT 60K 1L
Reference weight:	yes
Conversion function:	yes
Dispensing function:	yes
SLEEP function:	yes
Statistical function:	yes
Vibration-free weighing (Animal weighing program):	yes

P.O Box 25898 Sharjah United Arab Emirates

Phone : 06-5436933/06-5436733

Fax : 06-5437077

E-Mail:gentech@eim.ae Website: www.generaltech.ae