

### Elitech ILD-300 | Infrared Refrigerant Leak Detector | Detect All HFC, CFC, HCFC, HFO And Blends

For all common refrigerants, including CFC, HFC, HCFC, PFC, and HFO, the Elitech ILD-300 with leak detector comes with a carrying case, UV light, charging cord, power adaptor, and replacement filters. The best sensor in the leak detection system is the infrared sensor, which has an undegradable sensitivity, a long service life of over ten years, and the ability to reduce false alarms. Furthermore, the detector optimizes the user experience and shows the detection findings in a more diverse and intuitive manner thanks to its unique ergonomic design, gas selection, peak record, and huge TFT LCD screen. You will be well-equipped to perform efficient, dependable leak detection with ILD-300.



| Specifications      | Details                                                            |
|---------------------|--------------------------------------------------------------------|
| Sensor Type         | Infrared                                                           |
| Detection           | R134a, R410A, R32, R22, HFO-1234 and all HFCs, HCFCs, CFCs, PFCs.  |
| Power Supply        | Built-in lithium battery 3.7V 3000mA                               |
| Battery Life        | Up to 6 hours continuously                                         |
| Charging time       | Within 4hrs                                                        |
| Storage Temperature | -20Â°C~ 60Â°C (-4Â°F~ 140Â°F)                                      |
| Operates between    | Temperature: -10Â°C~ 52Â°C (-4Â°F~ 140Â°F)<br>Humidity: 50%~85% RH |
| Dimensions          | 95*45*190mm (3.75*1.76*7.50in.)                                    |
| Weight              | 415g (14.6oz)                                                      |