

UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com Tel:+966 (0) 3 834 4264

Tel: +966 (0) 3 834 4264 Fax: +966 3 834 4538

Kennedy 4 No2PT SPARK RESISTANT C/POINT SCREWDRIVER Be-Cu

Crosspoint Spark-resistant tools are used to eliminate the chances of accidental fires or explosions in potentially combustible or explosive environments. They resist the sparks that a standard tool could potentially create when striking hard surfaces. The use of spark resistant tools is essential in many industrial applications such as petroleum and chemical manufacturing, spray booth operations, the marine industry, the mining industry, the paper industries, or any location where flammable vapours or combustible residues are present. Beryllium Copper are manufactured to 30-10HRC and offer a breaking strain of 1117 N/m - 1236 N/m. Spark-resistant tools must be maintained with special care. Frequent cleaning/re-dressing to remove ferrous particles or contaminants, which may impair the spark resistant properties, is essential.



Specifications	Details
Brand	Kennedy
Material	Beryllium Copper
Weight Each	75 g
Tip Size	No.2
Blade Length	100 mm
Tip Type	Crosspoint