


PK5520

PK-400-SFG14-PSPKG/US/ IW

Pressure sensors



1: sealing FPM / DIN 3869-14



Product characteristics

Electronic pressure monitor

Connector

Process connection: G ¼ A / M5 I

1 switching output

Measuring range: 0...400 bar / 0...5800 psi

Application

Application	Type of pressure: relative pressure Liquids and gases	
Pressure rating	600 bar	8700 psi
Bursting pressure min.	1600 bar	23200 psi
Medium temperature [°C]	-25...80	

Electrical data

Electrical design	DC PNP	
Operating voltage [V]	9.6...32 DC	
Current consumption [mA]	< 25	
Insulation resistance [MΩ]	> 100 (500 V DC)	
Protection class	III	
Reverse polarity protection	yes	

Outputs

Output	1 switching output	
Output function	normally open	
Current rating [mA]	500	
Voltage drop [V]	< 2	
Short-circuit protection	pulsed	
Overload protection	yes	
Switching frequency [Hz]	100	

Measuring / setting range

Measuring range	0...400 bar	0...5800 psi
Setting range		
Set point, SP	12...400 bar	175...5800 psi
Hysteresis	8 bar	116 psi

Accuracy / deviations

Deviations (% of value of measuring range)

PK5520

PK-400-SFG14-PSPKG/US/ IW

Pressure sensors

Switch point accuracy	< ± 2.5 *)
Characteristics deviation	< ± 1.5 (BFSL) / < ± 2.5 (LS) **)
Repeatability	< ± 0.5
Temperature drift (/ 10 K)	< ± 0.5
in the temperature range [°C]	0...80

Software / programming

Adjustment of the switch point	setting ring
--------------------------------	--------------

Environment

Ambient temperature [°C]	-25...80
Storage temperature [°C]	-40...100
Protection	IP 67

Tests / approvals

EMC	EN 61000-4-2 ESD: 4 kV CD / 8 kV AD EN 61000-4-3 HF radiated: 10 V/m EN 61000-4-4 Burst: 2 kV EN 61000-4-6 HF conducted: 10 V
Shock resistance	DIN IEC 68-2-27: 50 g (11 ms)
Vibration resistance	DIN IEC 68-2-6: 20 g (10...2000 Hz)
MTTF [Years]	704

Mechanical data

Process connection	G ¼ A / M5 I
Materials (wetted parts)	stainless steel 316L / 1.4404; FPM (Viton)
Housing materials	PBT (Pocan); PC (Makrolon); FPM (Viton); stainless steel 316L / 1.4404
Switching cycles min.	50 million
Tightening torque [Nm]	25
Weight [kg]	0.094


Displays / operating elements

Display	Operation LED green Switching status LED yellow
---------	--

Electrical connection

Connection	M12 connector
------------	---------------

Wiring



Remarks

Remarks	*) Setting accuracy **) BFSL = Best Fit Straight Line / LS = Limit Value Setting
Pack quantity [piece]	1